
imonod **o** 


**BOILER DRAIN VALVES** 

## **BOILER DRAIN VALVE**

776200









- M/F boiler drain valve with operating key in cap
- Finishing nickel-plated
- Thread ISO 228
- Temperature range min-10°C max +120°C

Valve suitable for interrupting fluids that are generally non-corrosive, compatibly with the valve materials.

Plumbing and heating systems are the ideal fields of application, where this valve is used to unload heat transfer fluids from the heating system.

It's a reduced bore valve and the ball seal is guaranteed by two PTFE seats.

The operating mechanism seal features two O-Rings with an internally installed stem and anti-ejection system.

It is advisable to carry out a complete maneuver cycle at least once every three months in order to prevent limescale deposits that could compromise the valve functioning.

## COMPONENTS

POS:	PART NAME	N°	MATERIAL
1	Body	1	CW617N UNI-EN 12165 nickel-plated
2	Seal	2	PTFE
3	Ball	1	CW617N UNI-EN 12164 chrome-plated
4	End connection	1	CW617N UNI-EN 12165 nickel-plated
5	Stem	1	CW617N UNI-EN 12164
6	0-Ring	2	EPDM 70 Perox
7	Gasket	1	SBR
8	Plug	1	CW617N UNI-EN 121645 nickel-plated
9	Chain	1	Iron

## **DIMENSIONS**

DN	Α	В	С	D	E	R	PM	
15	1/2"	3/4"	51	46	15	3/4"	40	

## PACKAGING

CODE	77620004
PCS BOX	10
PCS CARTON	100