

COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

# **MALE STRAIGHT FITTING**

3892







# WATER COMPRESSION FITTINGS

- Male straight compression fitting with O-Ring
- Thread ISO 228
- Maximum operating pressure: 10 bar
- Temperature range min 0°C max +95°C

Fitting suitable for distributing fluids that are generally noncorrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, air-conditioning and distribution of drinking water.

**b**onom

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

## COMPONENTS

| POS. | PART NAME           | N° | MATERIAL                          |
|------|---------------------|----|-----------------------------------|
| 1    | Fitting             | 1  | CW617N UNI-EN 12164 nickel-plated |
| 2    | 0-Ring              | 2  | EPDM Perox                        |
| 3    | Washer              | 1  | PTFE                              |
| 4    | 0-Ring (18,77x1,78) | 2  | EPDM Perox                        |
| 5    | Ogive               | 1  | CW617N UNI-EN 12164               |
| 6    | Nut                 | 1  | CW617N UNI-EN 12165 nickel-plated |
|      |                     |    |                                   |

## DIMENSIONS

| A    | R    | В  |  |
|------|------|----|--|
| 16x2 | 1/2" | 38 |  |
| 20x2 | 1/2" | 41 |  |

### PACKAGING

|            | 16 - 1/2" | 20 - 1/2" |
|------------|-----------|-----------|
| CODE       | 38921604  | 38922004  |
| PCS BAG    | 10        | 10        |
| PCS CARTON | 250       | 150       |