



COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

FEMALE STRAIGHT FITTING

3902



- Female straight compression fitting
- Thread EN 10226-1
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water.

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS

| POS. | PART NAME | N° | MATERIAL |
|------|-----------|----|-----------------------------------|
| 1 | Fitting | 1 | CW617N UNI-EN 12165 nickel-plated |
| 2 | O-Ring | 2 | EPDM Perox |
| 3 | Washer | 1 | PTFE |
| 4 | Ogive | 1 | CW617N UNI-EN 12164 |
| 5 | Nut | 1 | CW617N UNI-EN 12165 nickel-plated |

DIMENSIONS

| A | R | B |
|------|------|------|
| 16x2 | 1/2" | 37 |
| 16x2 | 3/4" | 39,5 |
| 18x2 | 1/2" | 35 |
| 18x2 | 3/4" | 37 |
| 20x2 | 1/2" | 37,5 |
| 20x2 | 3/4" | 40 |
| 26x3 | 3/4" | 41 |
| 26x3 | 1" | 45,5 |
| 32x3 | 1" | 50 |

PACKAGING

| | 16 - 1/2" | 16 - 3/4" | 18 - 1/2" | 18 - 3/4" | 20 - 1/2" | 20 - 3/4" | 26 - 3/4" | 26 - 1" | 32 - 1" |
|-------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| CODE | 39021604 | 39021606 | 39021804 | 39021806 | 39022004 | 39022006 | 39022606 | 39022608 | 39023208 |
| PCS BAG | 10 | 10 | 10 | 10 | 10 | 10 | 5 | 5 | 5 |
| PCS CARTON | 200 | 180 | 200 | 150 | 150 | 150 | 100 | 80 | 50 |