



COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

# INTERMEDIATE STRAIGHT FITTING

3903



- Intermediate straight fitting
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water. The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

### COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165 (hot pressed) nickel-plated - CW617N UNI-EN 12164 (from bar) nickel-plated
2	O-Ring	4	EPDM Perox
3	Washer	2	PTFE
4	Ogive	2	CW617N UNI-EN 12164
5	Nut	2	CW617N UNI-EN 12165 nickel-plated

### DIMENSIONS

A	A1	B
16x2	16x2	42
18x2	18x2	46
20x2	16x2	47
20x2	20x2	52
26x3	16x2	53
26x3	26x3	58
32x3	32x3	75

### PACKAGING

	16 - 16	18 - 18	20 - 16	20 - 20	26 - 16	26 - 26	32 - 32
CODE	39031616	39031818	39032016	39032020	39032616	39032626	39033232
PCS BAG	10	10	10	10	5	5	2
PCS CARTON	200	150	100	120	70	70	30