



PRESS FITTINGS FOR PEX-AL-PEX PIPES

## CAP FITTING

4009



- Cap press fitting for pipe installation test
- Maximum operating pressure 10 bar
- Temperature range min 0°C – max +95°C
- The jaws for the fittings pressing have to be **TH** profile.

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, air-conditioning and distribution of drinking water. The tightness is guaranteed by two EPDM PEROX O-Rings, particularly recommended with water-glycol solutions, with a maximum glycol presence of 50%. The steel sleeve pressing, carried out with electromechanical tools, ensures a perfect and indivisible crimping to the pipe as well as an excellent resistance to external stress.

## ACS

### COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Cap fitting	1	CW617N UNI-EN 12164
2	O-Ring	2	EPDM Perox
3	Washer	1	PTFE
4	Bushing	1	AISI 304 stainless steel

### DIMENSIONS

A	B
16	35
18	35
20	35
26	35
32	36

### PACKAGING

	16	18	20	26	32
<b>CODE</b>	<b>40091600</b>	<b>40091800</b>	<b>40092000</b>	<b>40092600</b>	<b>40093200</b>
PCS BAG	10	10	10	10	10
PCS CARTON	300	200	200	150	100