


imonod **o** 


PRESS FITTINGS FOR PEX-AL-PEX PIPES

## INTERMEDIATE TEE FITTING

4031







- Intermediate tee press fitting
- Maximum operating pressure 10 bar
- Temperature range min 0°C max +95°C
- The jaws for the fittings pressing have to be **TH** profile.

Fitting suitable for distributing fluids that are generally noncorrosive, compatibly with the fitting materials.

Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, airconditioning and distribution of drinking water.

The tightness is guaranteed by two EPDM PEROX O-Rings, particularly recommended with water-glycol solutions, with a maximum glycol presence of 50%.

The steel sleeve pressing, carried out with electromechanical tools, ensures a perfect and indivisible crimping to the pipe as well as an excellent resistance to external stress.

# **ACS**

### COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165
2	O-Ring	6	EPDM Perox
3	Washer	3	PTFE
4	Bushing	3	AISI 304 stainless steel

#### **DIMENSIONS**

A	A1	A2	В	С	
26	32	26	112	55	
32	20	20	110	55	
32	20	26	110	55	
32	16	32	110	55	
32	18	32	110	55	
32	20	32	110	55	
32	26	26	110	55	
32	26	32	110	55	
32	32	32	110	55	

FOLLOWING THE DIMENSIONS FROM 40 TO 50

### PACKAGING

	26 - 32 - 26	32 - 16 - 32	32 - 18 - 32	32 - 20 - 20	32 - 20 - 26	32 - 20 - 32	32 - 26 - 26	32 - 26 - 32	32 - 32 - 32
CODE	4031263226	4031321632	4031321832	4031322020	4031322026	4031322032	4031322626	4031322632	4031323232
PCS BAG	2	2	2	2	2	2	2	2	2
PCS CARTON	30	30	30	30	30	30	30	30	30