



WATER BALL VALVES

NIAGARA

7730



- M/F miniball valve with screwdriver slot
- Thread ISO 228
- Temperature range min -10°C - max +90°C
- Normal pressure max 10 bar

Valve suitable for distributing and interrupting fluids that are generally non-corrosive, compatibly with the valve materials. Excellent fields of application are in plant engineering for plumbing, heating and pneumatics and industry, when it is necessary to have a shut-off element with reduced dimensions. It is a reduced-bore valve, and ball seal is provided by two PTFE seats. The operating mechanism seal features an O-Ring with an internally installed stem and anti-ejection system.

It is advisable to carry out a complete maneuver cycle at least once every three months in order to prevent limescale deposits that could compromise the valve functioning.

COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Body	1	CW617N UNI-EN 12164 chrome-plated
2	Seal	2	PTFE
3	Ball	1	CW617N UNI-EN 12164 nickel-plated
4	Ring nut	1	CW617N UNI-EN 12164
5	Stem	1	CW617N UNI-EN 12164 nickel-plated
6	O-Ring	1	NBR

DIMENSIONS

DN	A	B	D	PN
8	1/4"	39	8	10
10	3/8"	40	8	10
15	1/2"	45	10	10
20	3/4"	51	12	10

PACKAGING

	1/4"	3/8"	1/2"	3/4"
CODE	77300002	77300003	77300004	77300006
PCS BOX	30	30	25	15
PCS CARTON	300	300	250	150