

WATER BALL VALVES

NIAGARA DZR

7736




- DZR M/M miniball valve with lever
- Thread ISO 228
- Temperature range min -10°C - max +90°C
- Normal pressure max 10 bar



This valve is particularly indicated for distributing and shutting off fluids that can cause dezincification problems. Excellent fields of application are in plant engineering for plumbing, heating, pneumatics and industry, when it is necessary to have a shut-off element with reduced dimensions.

It is a reduced-bore valve, and ball seal is provided by two PTFE seats. Seal of the stem is provided by an O-Ring with the stem mounted from inside and a bottom-loaded system.

It is advisable to carry out a complete maneuver cycle at least once every three months in order to prevent limescale deposits that could compromise the valve functioning.




COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Body	1	CW511L UNI-EN 12164 chrome-plated
2	Seal	2	PTFE
3	Ball	1	CW511L UNI-EN 12164 nickel-plated
4	End connection	1	CW511L UNI-EN 12164 chrome-plated
5	Stem	1	CW511L UNI-EN 12164 nickel-plated
6	O-Ring	1	EPDM Perox
7	Screw	1	C4C UNI-EN 10263-03
8	Black plastic lever	1	NYLON PA66 + Glass fiber

DIMENSIONS

DN	A	Ø	B	C	D	PN
15	1/2"	15	44	28	10	10



PACKAGING

	1/2"
CODE	77360004
PCS BOX	5
PCS CARTON	100