

STOP VALVES

ANGLE-SEAT VALVE

7495



- F/F angle-seat valve with fixed stem and with drain cock
- Female thread EN10226-1
- Temperature range min 0°C - max +95°C

Valve suitable for distributing and interrupting fluids that are generally non-corrosive, compatibly with the valve materials. Plumbing and heating systems and industrial sector are the ideal fields of application.

Valve produced according to German standards DIN 3502 and 3546 SECTION II.

The seat tightness is guaranteed by a EPDM PEROX seal, approved by KTW.

COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Body	1	CW617N UNI-EN 12165
2	Upper part body	1	CW617N UNI-EN 12164 - CW617N UNI-EN 12165
3	O-Ring	1	KTW approved EPDM Perox
4	Upper part stem	1	CW617N UNI-EN 12164
5	Snap ring	1	Phosphorous bronze
6	O-Ring	2	KTW approved EPDM Perox
7	Valve	1	CW617N UNI-EN 12164
8	O-Ring	1	KTW approved EPDM Perox
9	Hose end disc	1	CW617N UNI-EN 12164
10	Gasket	1	KTW approved EPDM Perox
11	Washer	1	CW508L UNI-EN 1652
12	Self-locking nut	1	Brass
13	Handwheel	1	Plastic
14	Screw	1	CW508L UNI-EN 12166
15	Plug	1	CW617N UNI-EN 12164
16	O-Ring	2	KTW approved EPDM Perox
17	Vent nozzle	1	CW617N UNI-EN 12164

DIMENSIONS

DN	A	B	C	D	E	F	PN
15	Rp 1/2"	65	79	50	93	56	16
20	Rp 3/4"	75	90	50	106	62	16
25	Rp 1"	90	103	55	123	68	16
32	Rp 1.1/4"	110	125	70	150	74	16
40	Rp 1.1/2"	120	136	70	163	79	16
50	Rp 2"	150	153	70	188	89	16

PACKAGING

	Rp 1/2"	Rp 3/4"	Rp 1"	Rp 1.1/4"	Rp 1.1/2"	Rp 2"
CODE	74950004	74950006	74950008	74950010	74950011	74950013
PCS BOX	-	-	-	-	-	-
PCS CARTON	70	50	30	20	15	10