



Vitoni

VITONE TRE PEZZI

2470



- Vitone a tre pezzi ad asta fissa
- Filettatura maschio ISO 228
- Intervallo di temperatura min 0°C - max +95°C

COMPONENTI

| POS. | DESCRIZIONE | N° | MATERIALE |
|------|------------------------------|----|---------------------|
| 1 | Corpo vitone | 1 | CW617N UNI-EN 12164 |
| 2 | O-Ring vitone | 1 | NBR |
| 3 | O-Ring vite | 1 | NBR |
| 4 | Vite | 1 | CW617N UNI-EN 12164 |
| 5 | Anello elastico | 1 | Bronzo fosforoso |
| 6 | Valvolina | 1 | CW617N UNI-EN 12164 |
| 7 | O-Ring valvolina (solo 1/2') | 1 | NBR |
| 8 | Guarnizione | 1 | NBR |
| 9 | Dado | 1 | CW617N UNI-EN 12164 |

MISURE

| A | B min | B max | C | D (Broccia) | E | PN |
|------|-------|-------|------|-------------|-------|----|
| 3/8" | 16,3 | 22,5 | 26 | 8x20 | M21x1 | 16 |
| 1/2" | 16,8 | 23,5 | 30,5 | 8x20 | M24x1 | 16 |

IMBALLAGGIO

| | 3/8" | 1/2" |
|---------------|-----------------|-----------------|
| CODICE | 24700003 | 24700004 |
| PZ SCATOLA | - | - |
| PZ CARTONE | 500 | 400 |